



boardwalk

Powered by **TimberTech**

TECHNICAL SPECIFICATION

For more information please visit our website
www.composite-prime.com

0113 426 2770



**TIMBER
DEVELOPMENT
UK** MEMBER



**The Association of
Professional
Landscapers**


TECHNICAL SPECIFICATION

Test		Test Method	Results	
Flame Spread Index		ASTM E84	100	
Coefficient of Thermal Expansion	Width	ASTM D696	6.1 x 10-5 mm/mm/°c	
	Length		4.7 x 10-5 mm/mm/°c	
Flexural	MOE (Elasticity)	ASTM D6109 ⁽¹⁾	576000 psi	3969 MPa
	MOR (Rupture)		1640 psi	11.3MPa
Specific Gravity		ASTM D 792	1.2 gm/cc ³	
Fungus Resistance		ASTM D 1413	rating = no decay	
Water Absorption	% mass	ASTM D1037	<2.0%	
	% width		<2.0%	



These specifications represent the result of Intertek evaluation of Boardwalk to the requirements of the standards listed above.

Board Dimensions: 24 x 136 x 4880mm
*The below diagrams illustrate the two different shapes of board available.



COLOUR RANGE

Boardwalk is available in three traditional woodgrain colours, to enhance your outdoors: Weathered Oak, Natural Oak and Dark Oak.

